

# HydRo Glasadditiv

## Technical information

- Characteristics:** **HydRo Glasadditiv** is a paint additive for **HydRo Colour Plus** and **HydRo Möbel Lack Plus 1K/2K** for direct coating on glass.  
A perfect result can only be achieved if the following instructions are observed.
- Application area:** To achieve the glass adhesion of **HydRo Colour Plus** and **HydRo Möbellack Plus 1K/2K**.  
Attention: Not suitable for solvent-based systems!  
No warranty can be given for use in third-party products.
- Substrates:** Perfectly dry, clean and degreased glass surfaces. Before painting, it is essential to clearly determine which side of the glass surface can be painted over (e.g. using a suitable measuring device to recognise the tin bath side of float glass). suitable measuring device to recognise the tin bath side of float glass), as it is generally not possible to paint over the tin bath side.
- Mixing ratio:** 1% to the base coat
- Application:** See technical information for master material.  
Caution: Do not use too small quantities, as this reduces the dosing accuracy.
- Spreading rate:** See technical information for base material.
- Cleaning of tools:** See technical information master material.
- Storage:** Max. 12 months in the original sealed container.
- Notes:** Storage for at least 1 year in the original sealed container.  
Store and transport **HydRo Glasadditiv** in a cool place, but not below +6°C. Close opened containers tightly. If the air space in the container is too large, transfer to a smaller container (do not use tin containers due to the risk of rust).
- Please consider:** The product and the information in this data sheet correspond to the current state of the art. Our written and verbal application recommendations, which are based on our experience and to the best of our knowledge, are non-binding and do not constitute a contractual legal relationship or any ancillary obligation arising from the purchase contract. They do not release the Application from his obligation to check the existing substrate and the suitability of our products for the intended use on his own responsibility. In case of doubt, suitability and consumption quantities must be checked by applying a sample surface. If third-party products are mixed with our products, or if they are applied together with third-party products, we can not guarantee that the surface finish of the surface will be flawless. Application of our products is subject to the German Construction Contract Procedures (VOB). Our general terms of delivery and payment apply.

This information sheet supersedes all previous information sheets.

Edited 04/24