



RoCryl Lichtschutzadditiv

Technical data sheet

- Characteristics:** Additive to increase the light fastness of solventborne coatings.
A perfect result can only be achieved by carrying out the following instructions.
- Application area:** **RoCryl Lichtschutzadditiv** is used to increase the light fastness of solventborne paints.
Attention: Not suitable for waterborne systems!
There is no guarantee when used with third-party products.
- Mixing ratio:** Add 5-10% by weight to the paint before adding the hardener.
- Application:** See technical data sheet of the main product.
Attention: Do not prepare too little quantities, as this may affect the dosing accuracy.
- Cleaning tools:** **Waschlöser Nr. 52** and **PUG Pinsel- u. Gerätereiniger**
- Storage:** For at least 3 years in unopened original container.
- Please consider:** The product and the recommendations in this technical data sheet correspond to today's state of the art. Our oral and written application recommendations, that are based on years of experience and provided to the best of knowledge, are non-committal and do not establish a contractual relationship and secondary obligation of the sales contract. They do not release the user from his obligation to verify on his own responsibility the existing substrate and the suitability of our products for the intended purpose. In case of doubt, suitability and spreading rate are to be tested by creating a sample. If our products are combined or intermixed with third-party products, we cannot guarantee a perfect surface finish.
Our general terms and conditions apply.

This technical data sheet replaces all previous versions.

Edited 10/20